

DEVELOPMENT OF CHITOSAN/ALGINATE/SILVER NANOPARTICLES
HYDROGEL SCAFFOLD FOR SOFT TISSUE ENGINEERING APPLICATIONS

ROSLINDA HANI BINTI RAMLI

A thesis submitted in
fulfillment of the requirement for the award of the
Degree of Master of Mechanical Engineering with Honours

Faculty of Mechanical and Manufacturing Engineering
Universiti Tun Hussein Onn Malaysia

AUGUST 2017

This thesis is dedicated to

My father, Ramli B. Mohammed

My mother, Rosiyah Bt. Suratman

Husband, Muhammad Basry Bin Mahsun

*Little caliph in my womb that go through this thesis writing and project with me and
safely born during my thesis writing period, Muhammad Haqem Naufal Bin*

Muhammad Basry

My siblings, Roslina Hanim Ramli, Rafizul Hafiz Ramli and Rafirul Hanif Ramli

My family in-laws

My Project Supervisor and Co-Supervisor, Associate Professor Dr. Anika Zafiah

Mohd Rus and Associate Professor Dr. Soon Chin Fhong

And all my colleagues and friends.



LIST OF ASSOCIATED PUBLICATIONS

Conference Papers

1. Synthesis of Chitosan/Alginate/Silver Nanoparticles Hydrogel Scaffold. Ramli, R. H., Soon, C. F., & Rus, A. Z. M. (2016). Green Design and Manufacture Internationaal Conference, Phuket, 1-2 May 2016. In *MATEC Web of Conferences* (Vol. 78, p. 01031). EDP Sciences.
2. Characterisation of silver nanoparticles produced by three different methods based on Borohydride reducing agent. Ramli, R. H., Soon, C. F., & Rus, A. Z. M. (2016). Green Design and Manufacture Internationaal Conference, Phuket, 1-2 May 2016. In *MATEC Web of Conferences* (Vol. 78, p. 01032). EDP Sciences.

ACKNOWLEDGEMENT

Alhamdulillah, all praises to Allah that I finally able to finish my master's study. First of all, I would like to express my sincere appreciation to my supervisor and co supervisor, Associate Prof. Dr. Anika Zafiah Mohd. Rus and Associate Prof. Dr. Soon Chin Fhong for the support given throughout the duration for this research. Without their continuous support and patience throughout this research and thesis writing, I will not be able to complete it on time.

I also would like to express my appreciation especially to MyBrain15, Universiti Tun Hussein Onn Malaysia and GIPS Vot U337 for funding me financial support during the study. Many thanks to all my colleagues in this university that always help me and provide any support throughout this research, Arina Basyirah, Nurul Hamizah, Wong and Leong. I would also like to thank to the technicians involved in this research, Madam Faezahana, Miss Isrihetty and Mr. Fazlan.

In addition, I would like to thank to Microelectronics and Nanotechnology-Shamsudin Research Centre (MiNT-SRC) and Faculty of Mechanical Engineering (FKMP) of UTHM for providing the facilities for me to conduct this research. Appreciation also goes to everyone involved directly or indirectly towards the compilation of this thesis. Last but not least, author would specially thank to beloved parents, husband, families and friends. Without their moral support, author will not have the courage to continue the study and completed the thesis.

ABSTRACT

A biodegradable scaffold in tissue engineering serves as a temporary skeleton to accommodate and stimulate new tissue growth. Alginate (Alg) and chitosan (Chi) are both popular materials applied as biomaterials or bioimplants. However, Alg derived from brown algae is highly compliant and easily decomposed in fluid, whilst Chi derived from shrimp shells has weak strength. In rectify these problems, the development of Chi and Alg based biodegradable scaffolds incorporated with silver nanoparticles (AgNPs) with enhanced mechanical properties and biosafe function is proposed. Different ratios of chitosan/alginate (Chi/Alg) were prepared and the effect of different ratio (1:1, 1:2 and 2:1) to the mechanical, biological properties with and without AgNPs and keratinocyte cell growth were investigated. The preliminary result of FTIR, UV-Vis, XRD, FESEM and EDS proved the production of silver nanoparticles. Meanwhile, FTIR, swelling/degradation, DMA, TGA, DSC, FESEM and MTT assay was conducted to study the properties of Chi/Alg based scaffold. FTIR analysis shows the crosslinking of Chi/Alg based scaffold. Swelling/degradation and DMA shows Chi/Alg and chitosan/alginate/silver nanoparticles (Chi/Alg/AgNPs) has adequate swelling and compressive modulus that exceed the epidermis' Young modulus, thus able to provide mechanical support upon application. Meanwhile, the thermal analysis revealed that the onset decomposition temperature of scaffold were at around 70 °C which is due to the loss of water present in the scaffold thus thermally safe for soft tissue application. Based on FESEM result, there are different in surface structure of Chi/Alg based scaffold. Finally, with the incorporation of 0.3 % PVP synthesised AgNPs in Chi/Alg based scaffold, cells are able to live up to 14 days. As a result, Chi incorporation in the Alg and AgNPs improved physical, mechanical properties of hydrogel itself and provide biosafe environment during the study.

ABSTRAK

Di dalam kejuruteraan tisu, perancah atau acuan biodegradasi berfungsi sebagai struktur sementara untuk menampung dan merangsang pertumbuhan tisu baru. Antara bahan yang sering digunakan sebagai bio-bahan serta bio-implant adalah alginate (Alg) dan chitosan (Chi). Namun begitu, walaupun sifat Alg dan Chi yang kedua-duanya berasal dari bahan organik iaitu alga coklat dan kulit udang, Alg sangat mudah melarut di dalam cecair manakala Chi mempunyai kekuatan yang rendah. Maka, penggabungan Chi dan Alg serta nanopartikel perak (AgNPs) bagi membentuk perancah biodegradasi dilakukan untuk meningkatkan sifat mekanikal serta fungsi keselamatan biologi. Chitosan/alginate (Chi/Alg) dengan berbeza nisbah (1: 1, 1: 2 dan 2: 1) disediakan sama ada dengan penambahan atau tanpa penambahan AgNPs dan kesannya terhadap sifat mekanikal, biologi serta pertumbuhan sel keratinocyte telah disiasat. Keputusan awal FTIR, UV-Vis, XRD, FESEM dan EDS membuktikan penghasilan AgNPs. Manakala ujian FTIR, degradasi, DMA, TGA, DSC, FESEM dan MTT assay telah dijalankan untuk mengkaji sifat-sifat perancah biodegradasi Chi/Alg. Analisis FTIR menunjukkan Chi/Alg telah bergabung. Keputusan kadar pengembangan di dalam cecair dan DMA menunjukkan Chi/Alg dan Chi/Alg/AgNPs mempunyai kadar pengembangan yang seimbang dan modulus mampatan yang melebihi mampatan epidermis kulit dan seterusnya mampu member sokongan mekanikal sewaktu aplikasi penggunaan. Sementara itu, terma analisis mendedahkan bahawa suhu permulaan penguraian perancah berada di sekitar 70 ° C yang disebabkan oleh kehilangan air di dalam perancah, maka ia selamat digunakan. Berdasarkan keputusan FESEM, permukaan Chi/Alg juga berbeza. Tambahan lagi, penambahan 0.3 % PVP AgNPs dalam perancah Chi/Alg tidak memberikan kesan kepada sel kerana sel mampu untuk hidup sekurang-kurangnya selama 14 hari. Kesimpulannya, gabungan Chi dalam Alg dan AgNPs telah meningkatkan sifat fizikal, sifat mekanik hidrogel sendiri dan menyediakan persekitaran biologi yang selamat semasa kajian.

CONTENTS

TITLE	i
DECLARATION	ii
DEDICATION	iii
LIST OF ASSOCIATED PUBLICATIONS	iv
ACKNOWLEDGEMENT	v
ABSTRACT	vi
ABSTRAK	vii
CONTENTS	viii
LIST OF TABLES	xii
LIST OF FIGURES	xiii
LIST OF ABBREVIATIONS	xvii
 CHAPTER 1 INTRODUCTION	 1
1.1 Research background	1
1.2 Problem statement	3
1.3 Hypothesis of the research	4
1.4 Aim of research	5
1.5 Research objective	5
1.6 Scope of research	5
1.7 Thesis contribution	6
 CHAPTER 2 LITERATURE REVIEW	 7
2.1 Introduction	7
2.2 Tissue engineering	8
2.3 Skin and human keratinocytes	11
2.4 Hydrogel	13

2.5	Natural biopolymers in human physiological system	16
2.6	Synthetic biopolymers for application in tissue engineering	18
2.7	Biopolymers for application in tissue engineering	19
2.7.1	Chitosan	19
2.7.2	Alginate	21
2.8	Silver nanoparticles	27
2.9	Techniques for mechanical and physical characterisation of polymers	27
2.9.1	Thermal analysis of polymers	28
2.9.2	Chemical analysis of polymers	28
2.9.3	Mechanical analysis of polymers	29
2.9.4	Electron microscopy	30
2.10	Summary	33

CHAPTER 3 MATERIALS & METHODOLOGY 31

3.1	Introduction	31
3.2	Materials	33
3.3	Methodology	33
3.3.1	Synthesis of silver nanoparticles	33
3.3.2	Synthesis of chitosan/alginate hydrogel	35
3.3.3	Preparation of HaCaT Cells	38
3.4	Characterisation of the chitosan/alginate scaffold and silver nanoparticles	39
3.4.1	UV-VIS spectrophotomet	39
3.4.2	X-Ray diffraction (XRD)	40
3.4.3	Fourier transform infrared	40

spectroscopy (FTIR)

3.4.4 Swelling/degradation test 41

3.4.5 Dynamic mechanical analysis 41
(DMA)

3.4.6 Thermogravimetric analysis 42
(TGA)

3.4.7 Differential scanning calorimetry 43
(DSC)

3.4.8 Field emission scanning electron 44
microscopy (FESEM) and energy
dispersive X-Ray spectroscopy (EDS)

3.4.9 MTT assay 45

CHAPTER 4 RESULTS & DISCUSSION 47

4.1 Introduction 47

4.2 Characterisation of AgNPs 48

4.2.1 Functional groups of AgNPs 48

4.2.2 Optical properties of AgNPs 50

4.2.3 The crystalline structure of 51
AgNPs

4.2.4 The physical and elements of 53
AgNPs

4.3 Physical, chemical, thermal and surface 57
properties of hydrogel scaffold

4.3.1 Functional groups of Chi/Alg 57
based scaffold

4.3.2 Swelling/degradation result of 62
Chi/Alg scaffold

4.3.3 Compression properties of the 64
Chi/Alg scaffold

4.3.4	Thermal properties of the Chi/Alg scaffold	66
4.3.5	Morphology of the freeze-dried scaffold	73
4.4	Cell viability study of hydrogel seeded with HaCaT cells	82
CHAPTER 5	CONCLUSIONS	84
5.1	Conclusion	84
5.2	Future Works	85
	REFERENCES	86
	APPENDIX	97



PT TA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF TABLES

2.1	Classification of hydrogel	16
3.1	The sample designation of chitosan/alginate/silver nanoparticles	38
4.1	TGA result of hydrogel scaffold sample	68
4.2	Summary of surface morphology structure for different composition of scaffold	81



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF FIGURES

2.1	A schematic diagram for tissue engineering approaches	9
2.2	Structure of epidermis	12
2.3	The matrices in the extracellular matrices (ECM)	14
2.4	The structure of (a) physical and (b) chemical hydrogel	15
2.5	Chemical structure of chitosan	20
2.6	Schematic diagram of β -D-mannuronic acid (M units) and α -L-guluronic acid (G units) monomers, and a $-(G-M)-$ structure sodium alginate	22
2.7	Polyelectrolyte complex of chitosan/alginate	25
2.8	The antimicrobial activity of silver	26
3.1	Methodology flowchart of chitosan/alginate hydrogel scaffold & silver nanoparticles	32
3.2	The synthesis of silver nanoparticle solution	34
3.3	Hydrogel scaffold in dry form	36
3.4	Experiment flowchart for the synthesis of chitosan/alginate/silver nanoparticles	37
3.5	Chitosan/alginate scaffold upon DMA compression test	42
3.6	Thermobalance designs utilised in TGA	43
3.7	(a) Silver nanoparticles drop casted on copper tape upon testing and (b) Chitosan/alginate biocomposites coated with gold particles upon testing	45
3.8	Hydrogel samples seeded with cells cultured on 96 well plate and upon MTT assay testing	46
4.1	Chemical structure of PVP	48
4.2	FTIR spectra of pure PVP	49

4.3	FTIR spectra of pure PVP, AgNPs synthesised with 0.3 %, 0.5 % and 0.7 % of PVP	50
4.4	UV Vis absorption spectra of synthesised AgNPs with different PVP concentration (a) 0.3 % PVP (b) 0.5 % PVP (c) 0.7 % PVP and (d) Overlay UV Vis spectra of all PVP concentration	51
4.5	XRD patterns recorded for AgNPs in (a) 0.3 % , (b) 0.5 % and (c) 0.7% of PVP that were drop casted on a glass substrate	53
4.6	FESEM and EDS spectra of AgNPs in 0.3 % PVP drop-coated film on glass substrate	54
4.7	FESEM and EDS spectra of AgNPs in 0.5 % PVP drop-coated film on glass substrate	55
4.8	FESEM and EDS spectra of AgNPs in 0.7 % PVP synthesised drop-coated film on glass substrate	56
4.9	FTIR spectra of Chi scaffold	58
4.10	FTIR spectra of Alg scaffold	58
4.11	FTIR spectra of Chi/Alg (1:1) scaffold	59
4.12	FTIR spectra of calcium alginate (CaAlg), Chi/Alg (1:1), Chi/Alg (1:2) and Chi/Alg (2:1) scaffold	60
4.13	FTIR spectra of Chi/Alg (1:1), Chi/Alg (1:2), Chi/Alg (2:1) and Chi scaffold	61
4.14	FTIR spectra of AgNPs and Chi/Alg/AgNPs with different weight ratio of Chi and Alg	62
4.15	Weight loss of Chi/Alg scaffold of 2 months soaking in DMEM solution	63
4.16	Compressive modulus of freeze-dried hydrogel scaffold on temperature ramp mode at 50 °C	66
4.17	Derivative weight % versus temperature of Alg, Chi/Alg (1:1), Chi/Alg (1:2) and Chi/Alg (2:1)	69
4.18	Derivative weight % versus temperature of Chi/Alg/AgNPs (1:1), Chi/Alg/AgNPs (1:2) and Chi/Alg/AgNPs (2:1)	69
4.19	Weight % versus temperature of Alg, Chi/Alg (1:1), Chi/Alg (1:2) and Chi/Alg (2:1)	70

4.20	Weight % versus temperature of Chi/Alg/AgNPs (1:1), Chi/Alg/AgNPs (1:2) and Chi/Alg/AgNPs (2:1)	70
4.21	DSC thermograms of (a) Alg, (b) Chi/Alg (1:1), (c) Chi/Alg (1:2) and (d) Chi/Alg (2:1)	72
4.22	DSC thermograms of (a) Chi/Alg/AgNPs (1:1), (b) Chi/Alg/AgNPs (1:2) and (c) Chi/Alg/AgNPs (2:1)	73
4.23	FESEM image of cross-section of Alg scaffold (a) before Ca^{2+} crosslinking 50 \times , (b) after Ca^{2+} crosslinking 50 \times , (c) after Ca^{2+} crosslinking and seeded with cells 50 \times , (d) after Ca^{2+} crosslinking and seeded with cells 1000 \times	74
4.24	FESEM image of cross-section of chitosan scaffold (a) before immersed with DMEM solution 50 \times , (b) after immersed with DMEM solution 50 \times (c) after immersed with DMEM solution and seeded with cells 50 \times , (d) after immersed with DMEM solution and seeded with cells 1000 \times	75
4.25	FESEM image of cross-section of Chi/Alg (1:1) scaffold (a) before Ca^{2+} crosslinking 50 \times , (b) after Ca^{2+} crosslinking 50 \times , (c) after Ca^{2+} crosslinking and seeded with cells 50 \times , (d) after Ca^{2+} crosslinking and seeded with cells 1000 \times (e) with incorporation of AgNPs, after Ca^{2+} crosslinking and seeded with cells 50 \times and (f) with incorporation of AgNPs, after Ca^{2+} crosslinking and seeded with cells 1000 \times	76
4.26	FESEM micrographs of cross-section of Chi/Alg (1:2) scaffold (a) before Ca^{2+} crosslinking 50 \times (b) after Ca^{2+} crosslinking 50 \times (c) after Ca^{2+} crosslinking and seeded with cells 50 \times , (d) after Ca^{2+} crosslinking and seeded with cells 1000 \times (e) with incorporation of AgNPs, after Ca^{2+} crosslinking and seeded with cells 50 \times and (f) with incorporation of AgNPs, after Ca^{2+} crosslinking and seeded with cells 1000 \times	78
4.27	FESEM images of cross-section of Chi/Alg (2:1) scaffold (a) before Ca^{2+} crosslinking 50 \times , (b) after Ca^{2+} crosslinking 50 \times , (c) after Ca^{2+} crosslinking and seeded with cells 50 \times , (d) after	80

Ca²⁺ crosslinking and seeded with cells 1000 × (e) with incorporation of AgNPs, after Ca²⁺ crosslinking and seeded with cells 50 × and (f) with incorporation of AgNPs, after Ca²⁺ crosslinking and seeded with cells 1000 ×

- 4.28 Cell viability (MTT assay) result of absorbance vs ratio of hydrogel on 7th and 14th day



LIST OF ABBREVIATIONS

DMA	- Dynamic Mechanical Analysis
FTIR	- Fourier Transform Infrared Spectroscopy
DSC	- Differential Scanning Calorimetry
TGA	- Thermogravimetric Analysis
AFM	- Atomic Force Microscopy
SEM	- Scanning Electron Microscopy
PEG	- Polyethylene glycol
DI water	- Deionized water
PLA	- Poly(lactic acid)
PGA	- Poly(glycolic acid)
PLGA	- Poly(lactic-co-glycolic acid)
AgNPs	- Silver nanoparticles
Chit	- Chitosan
Alg	- Alginate

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Calculations	82



CHAPTER 1

INTRODUCTION

1.1 Research background

Every year, a large number of individuals are suffering from tissue impairment and organ malfunction due to the accident and illness (Adhikari *et al.*, 2016). This impaired tissues and aged cells are restored by the self-healing ability of human body. However, the restore capacity of these mature tissues is frequently inadequate if the injury caused severe damage (Upadhyay, 2015). Hence, synthetic devices, donor organs as well as autologous transplants are utilised to substitute unfixable harmed tissues and organs. However, these procedures failed to substitute the organ failure completely. Thus, the development of alternative strategies was caused by demand for transplantation of organs and tissue exceeding the supply (Rouchi & Mahdazvi-Mazdeh, 2015). Additionally, Ministry of Health (Malaysia) communicated that, up to 31 January 2015, practically 19 353 patients require organ transplantation and the organ transplantation rate in Malaysia is the lowest in the world which is 0.68 donor for every one million people. This issue is caused by the supply which is the donor organ that unable to fulfil the demand which is the increasing number of patients (Kementerian Kesihatan Malaysia, 2017).

At regular intervals based on U.S. Department of Health & Human Services, transplant waiting list is expanding and averagely 21 patients die while waiting for the transplantation (U.S. Department of Health & Human Services, 2016). The deficiency of organs or effective organ replacement has caused thousands die every year while waiting for transplantation. Approaches such as substituting impaired organ through mechanical approach (heart lung bypass machines and dialysis) and artificial devices (joint substitution) are short-term solutions used by the clinicians.

However, these approaches do not allow the patients to completely recover from their injury and may have several limitations to conduct their habitual activity. These methods also may cause the state of being infected and refusal act of the body to the foreign device upon transplantation (Orlando *et al.*, 2013). These issues need to be addressed by new development in the area of tissue engineering. Research on designing manufactured biomaterials that can supplant harmed or injured tissue for short-term and long-term substitution was conducted due to the necessity for substituting damaged tissue in human body (Park, 2011).

Biomaterial is any biocompatible material, natural or synthetically, that is used to supplant or part of an organ or its tissue, while in private contact with living tissue (Chen & Thouas, 2014). Biomaterials moreover defined as any substance (other than a prescription) or blend of substances, originated naturally or synthetically, which can be used for any time period, with clinical trials taken into account or as a part of a structure which treats, extends, or replaces any tissue (Censi, 2010). Hydrogel frameworks are one of various kinds of biomaterials that has been utilised broadly as part of tissue building applications (Park, 2011).

Due to its favorable characteristics, hydrogels have been applied widely in biomedical such as tissue engineering as well as drug delivery. Their high water content renders them great with living tissues and proteins and their viscoelasticity minimises damage to the encapsulating tissue. Hydrogels are commonly appealing in field of tissue engineering due to their mechanical properties alike to the natural tissues. The biodegradability properties of hydrogels permit the hydrogels transplantation into human body, without the need of second surgery after the hydrogel degraded in the body because the extracellular matrices by the incorporated cells after a period of time will replace the degraded hydrogel (Zhao *et al.*, 2015, Chai *et al.*, 2017).

In this project, chitosan/alginate based hydrogel with the inclusion of silver nanoparticles was proposed for application as a bio-scaffold in tissue engineering. Chitosan and alginate are natural occurring polymers and offer several advantages to mimic natural extracellular matrix (ECM) in the body. However, these two materials presented have certain drawbacks when used independently (Lanza, 2011; Kim, 2013; Szymanska, 2015). Silver nanoparticles were reported with antibacterial properties in past research (Thomas, 2015). When chitosan and alginate are mixed and incorporated with silver nanoparticles, it is believed that the produced hydrogel

composites scaffold will improve the mechanical properties, biocompatibility, biodegradability and cell growth during the *in-vitro* study as well provide biosafe environment for the growth of seeded human keratinocyte cell lines.

1.2 Problem statement

Alginate and chitosan has been utilised broadly as hydrogel framework either separately or by blended with different materials, for example, hyaluronidase enzyme core-5-fluorouracil-loaded chitosan/PEG/gelatine polymer nanocomposites (Rajan *et al.*, 2013), Chitosan-nanohydroxyapatite (Roy & Sailaja, 2015), Polycaprolactone-alginate (PCL-alginate) (Kim & Kim, 2015), and hydroxyapatite/chitosan-alginate (Han *et al.*, 2010) composite scaffolds for applications in tissue engineering. Chitosan has been broadly utilised as a part of the composites blended with collagen, coral and hydroxyapatite to grow new frameworks for tissue designing applications, however the mix of chitosan/alginate has not been much investigated (Lanza *et al.*, 2011). The major disadvantages of using chitosan alone as biopolymer are its weak physical strength (Kim, 2013), high swelling tendency (Agarwal & Murthy, 2015) and the restricted solubility of chitosan (Kim, 2013).

In overcome these problem, some chemical modification of chitosan either on $-NH_2$ groups of glucosamine units or on $-OH$ groups of the polymer, cross-linking and the incorporation with other materials was conducted to improve its properties to mimic the structure of the tissue (Saikia *et al.*, 2015; Aryaei, 2014; Jayakumar *et al.*, 2011, Rodríguez-Vázquez *et al.*, 2015). However, chitosan was found as an attractive natural biopolymer as it resembles glycosaminoglycan (GAGs) structure which is the main component of extracellular matrix (ECM) and its hydrophilic nature aids in cell adhesion, proliferation as well as differentiation. Besides that, chitosan also has aggregated polymeric chains which are compact thus provide stability to the scaffold in terms of application to be used in tissue engineering (Jayakumar *et al.*, 2011). In contrast, despite of being non-immunogenic, biocompatible and gentle gelling properties of alginate, alginate will be exposed to high degradability when exposed to fluid. The loss of divalent cations from alginate to the surrounding medium is uncontrollable, thus it caused hydrogel with unpredictable degradability ability, limited stability for long term effect as well as limited strength and toughness that

mainly depends on alginate's chemical structure (G content effect on stiffness) (Lee & Mooney, 2012; Sun & Tan, 2013).

In this research study, the development of chitosan/alginate hydrogel biocomposites for soft tissue engineering application mainly to improve the mechanical properties of the produced hydrogel itself will be conducted. This biocomposite with properties that complements each other is expected to improve mechanical and biophysical properties of the hydrogels. Silver nanoparticle is a non-toxic material and highly effective for antimicrobial activities. An addition of silver nanoparticles to the chitosan/alginate composites would create a compatible environment for the growth of seeded human keratinocyte cell lines.

1.3 Hypothesis of the research

The development of chitosan based hydrogel as natural based scaffold shows tremendous growth in the tissue engineering field. The disadvantage of chitosan in tissue engineering scaffolds is its limited solubility (Kim, 2013), stability and weak mechanical properties with range of 2.5 kPa modulus at 0.4 wt % of chitosan hydrogels (Mushi, 2014). Chitosan is an attractive natural biopolymer as it resembles GAGs of ECM that enhance the cell adhesion, proliferation and also differentiation to be used in tissue engineering application. However, chitosan has weak mechanical properties, limited solubility and stability (Kim, 2013). In contrast, even though alginate has simple gelling ability, biocompatible and non-immunogenic properties, alginate's drawback such as unpredictable degradability due to loss divalent cations and mechanical properties that depends on chemical structure of alginate has brought the effort to incorporate alginate with other materials to overcome its drawback (Lee & Mooney, 2012; Sun & Tan, 2013). Thus, by incorporating these two materials, chitosan/alginate hydrogel were believed to enhance the biocompatibility, solubility, and mechanical properties of the biocomposite to be used in soft tissue engineering application. Silver nanoparticles further added to improve the properties of hydrogel while ensuring the hydrogel is biosafe to be applied as implants later.

1.4 Aim of research

The aim of this research is to develop renewable source for damaged tissue with biocompatible, biodegradable and tunable mechanical properties. In this work, hydrogel scaffolds by using natural (chitosan & alginate) polymer derivatives with incorporation of silver nanoparticles were synthesised and characterised for tissue engineering applications.

1.5 Research objective

- i. To synthesise silver nanoparticles (AgNPs).
- ii. To synthesise chitosan/alginate hydrogel scaffolds with incorporation of silver nanoparticles.
- iii. To characterise physical and mechanical properties of chitosan/alginate hydrogel with/without inclusion of silver nanoparticles.
- iv. To investigate the effect of an addition of silver nanoparticle in chitosan/alginate with the seedings of human keratinocyte cell lines (HaCaT).

1.6 Scope of research

This research focused on developing hydrogel scaffold by mixing different biopolymers with different ratio and examining the mechanical and biophysical properties of the chitosan/alginate scaffold with an inclusion of silver nanoparticles. The silver nanoparticles also synthesised based on previous research (Malina *et al.*, 2012) and applied in this work. Functional groups of the scaffold were studied using Fourier Transform Infrared Spectroscopy (FTIR). While mechanical properties of materials were measured by Dynamic Mechanical Analyses (DMA). Thermal stability and decomposition of the hydrogel were conducted by Thermogravimetric Analysis (TGA) and Differential Scanning Calorimetry (DSC) respectively. Molecular surface structures were investigated by using Field Emission Scanning Electron Microscopy (FESEM). Apart from that, cell viability was studied by using MTT assay analysis. Swelling and degradation of the produced hydrogel were also being investigated.

1.7 Thesis contribution

In this dissertation, biosafe chitosan/alginate composites with the incorporation of silver nanoparticles finally produced. The characterisation of chitosan/alginate and chitosan/alginate/silver nanoparticles by different methods has been investigated and the main contribution of this research is by investigating the effect of addition of silver nanoparticles into chitosan/alginate based biocomposites to the human skin cells seeding as well as the study of its mechanical properties that has not been explored before. This result can be further used for other applications of tissue engineering.



CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

Chapter 2 presented the literature studies on tissue engineering, especially in soft tissue engineering (Section 2.2). In this sub section, the literature studies presented the history of tissue engineering, the approach and the materials that were incorporated in the area. The structure of skin and human keratinocytes were discussed in Section 2.3. Section 2.4 presented the physical and chemical properties of hydrogels and natural extracellular matrix (ECM) while Section 2.5 and 2.6 discussed on the natural biomaterials and synthetic biopolymers respectively. Section 2.7 meanwhile elaborated the biomaterials used in tissue engineering which chitosan (Section 2.7.1) and alginate (Section 2.7.2). Next, silver nanoparticles and its mechanism on antibacterial were discussed on Section 2.8. The mechanical and physical characterisation techniques such as thermal analysis, chemical analysis, mechanical analysis and electron microscopy were discussed in Section 2.9. And finally the summary of literature review is discussed on Section 2.10.

REFERENCES

- Abdelmonem, A. M. (2014). *Nanoparticles: Synthesis, Surface Modification and Functionalization for Biological and Environmental Applications*. Philipps-Universität Marburg University: Ph.D. Thesis.
- Adhikari, U., Rijal, N. P., Khanal, S., Pai, D., Sankar, J., & Bhattarai, N. (2016). Magnesium incorporated chitosan based scaffolds for tissue engineering applications. *Bioactive Materials*, 1(2), 132-139.
- Agarwal, S., & Murthy, R. S. R. (2015). Effect of different polymer concentration on drug release rate and physicochemical properties of mucoadhesive gastroretentive tablets. *Indian journal of pharmaceutical sciences*, 77(6), 705.
- Alasalvar, C., Miyashita, K., Shahidi, F., & Wanasundara, U. (Eds.). (2011). *Handbook of seafood quality, safety and health applications*. John Wiley & Sons.
- Ansell, J., & Rauscher, H. (2011). Report of the Joint Regulator-Industry Ad Hoc Working Group: Currently Available Methods for Characterization of Nanomaterials. Paris. *International Cooperation on Cosmetics Regulation (ICCR-5)*, from http://ec.europa.eu/consumers/sectors/cosmetics/files/pdf/iccr5_char_nano_en.pdf.
- Archana, D., Upadhyay, L., Tewari, R. P., Dutta, J., Huang, Y. B., & Dutta, P. K. (2013). Chitosan-pectin-alginate as a novel scaffold for tissue engineering applications. *Indian Journal of Biotechnology*, 12(4), pp. 475-482.
- Aryaei, A. (2014). *Mechanical properties of bio-nanocomposites and cellular behavior under mechanical stimulation*. University of Toledo: Ph.D. Thesis.
- Badawy, M. E., & Rabea, E. I. (2011). A biopolymer chitosan and its derivatives as promising antimicrobial agents against plant pathogens and their applications in crop protection. *International Journal of Carbohydrate Chemistry*, 2011.
- Barel, A. O., Courage, W., & Clarys, P. (1995). Suction method for measurement of skin mechanical properties: the cutometer. *Handbook for non-invasive methods and the skin*, 106, pp. 335-40.
- Barnes, H. A., Hutton, J. F., & Walters, K. (1989). *An introduction to rheology* (Vol. 3). Elsevier.

- Baysal, K., Aroguz, A. Z., Adiguzel, Z., & Baysal, B. M. (2013). Chitosan/alginate crosslinked hydrogels: Preparation, characterization and application for cell growth purposes. *International journal of biological macromolecules*, 59, 342-348.
- Bhat, S., & Kumar, A. (2012). Biomaterials in Regenerative Medicine. *Journal of Postgraduate Medicine Education and Research*, 46(2), 81-89.
- Bolsover, S. R., Shephard, E. A., White, H. A., & Hyams, J. S. (2011). *Cell biology: a short course*: John Wiley & Sons.
- Boy, R. (2010). *Generic films and fibers from polysaccharides: chitosan and alginate*. Auburn University: Ph.D. Thesis.
- Brandl, K., & Beutler, B. (2013). Phenotypic Mutation 'phoebus'. Retrieved Jun 10, 2015, from https://mutagenetix.utsouthwestern.edu/phenotypic/phenotypic_rec.cfm?pk=359
- Burdick, J. A., & Mauck, R. L. (2010). *Biomaterials for tissue engineering applications: a review of the past and future trends*: Springer Science & Business Media.
- Cao, N. (2011). *Fabrication of alginate hydrogel scaffolds and cell viability in calcium-crosslinked alginate hydrogel*. University of Saskatchewan: Master's Thesis.
- Callister, W. D., & Rethwisch, D. G. (2011). *Materials science and engineering* (Vol. 5). John Wiley & Sons.
- Censi, R. (2010). Temperature sensitive hydrogels for protein delivery and tissue engineering. Chai, Q., Jiao, Y., & Yu, X. (2017). Hydrogels for biomedical applications: Their characteristics and the mechanisms behind them. *Gels*, 3(1), 6.
- Chalmers, J. M., & Meier, R. J. (Eds.). (2008). *Molecular characterization and analysis of polymers* (Vol. 53). Elsevier.
- Chapman, J., Regan, F., & Sullivan, T. (2012). *Nanoparticles in anti-microbial materials: Use and characterisation*: Royal Society of Chemistry.
- Chen, Q., & Thouas, G. (2014). *Biomaterials: A Basic Introduction*: CRC Press.
- Cioffi, N., & Rai, M. (Eds.). (2012). *Nano-antimicrobials: progress and prospects*. Springer Science & Business Media.

- Costa-Pinto, A. R., Martins, A. M., Castelhana-Carlos, M. J., Correlo, V. M., Sol, P. C., Longatto-Filho, A., & Neves, N. M. (2014). In vitro degradation and in vivo biocompatibility of chitosan–poly (butylene succinate) fiber mesh scaffolds. *Journal of Bioactive and Compatible Polymers*, 29(2), 137-151.
- D'Mello, S., Elangovan, S., Hong, L., Ross, R. D., Sumner, D. R., & Salem, A. K. (2015). Incorporation of copper into chitosan scaffolds promotes bone regeneration in rat calvarial defects. *Journal of Biomedical Materials Research Part B: Applied Biomaterials*, 103(5), 1044-1049.
- Dai, X. (2017). *Electrospun curcumin gelatin blended nanofibrous mats accelerate wound healing by Dkk-1 mediated fibroblast mobilization and MCP-1 mediated anti-inflammation* Technical University of Munich: Ph.D. Thesis.
- Dai, Z., Ronholm, J., Tian, Y., Sethi, B., & Cao, X. (2016). Sterilization techniques for biodegradable scaffolds in tissue engineering applications. *Journal of tissue engineering*, 7, pp. 1-13.
- Dhandayuthapani, B., Yoshida, Y., Maekawa, T., & Kumar, D. S. (2011). Polymeric scaffolds in tissue engineering application: a review. *International Journal of Polymer Science*, 2011.
- Diridollou, S., Patat, F., Gens, F., Vaillant, L., Black, D., Lagarde, J. M., ... & Berson, M. (2000). In vivo model of the mechanical properties of the human skin under suction. *Skin Research and technology*, 6(4), pp. 214-221.
- Dumitriu, S. (2004). *Polysaccharides: structural diversity and functional versatility*: CRC press.
- Dumitriu, S., & Popa, V. I. (2013). *Polymeric Biomaterials* (Vol. 1): CRC Press.
- Ebnesajjad, S. (Ed.). (2012). *Handbook of biopolymers and biodegradable plastics: properties, processing and applications*. William Andrew.
- El-Sherbiny, I. M., & Yacoub, M. H. (2013). Hydrogel scaffolds for tissue engineering: Progress and challenges. *Global Cardiology Science and Practice*, 38.
- Enderle, J. D., & Bronzino, J. D. (2012). *Introduction to biomedical engineering*: Academic press.
- Fisher, J. P., Mikos, A. G., & Bronzino, J. D. (2007). *Tissue engineering*: CRC Press.
- Francis, N. L. (2012). *Development of a Multi-Functional Biopolymer Scaffold for Neural Tissue Engineering*. Drexel University: Ph.D. Thesis.
- Garg, N., & Garg, A. (2010). *Textbook of endodontics*. Boydell & Brewer Ltd.

- Gazori, T., Khoshayand, M. R., Azizi, E., Yazdizade, P., Nomani, A., & Haririan, I. (2009). Evaluation of Alginate/Chitosan nanoparticles as antisense delivery vector: formulation, optimization and in vitro characterization. *Carbohydrate Polymers*, 77(3), pp. 599-606.
- Giri, N., Natarajan, R., Gunasekaran, S., & Shreemathi, S. (2011). ¹³C NMR and FTIR spectroscopic study of blend behavior of PVP and nano silver particles. *Archives of Applied Science Research*, 3(5), pp. 624-630.
- Gentile, P., Chiono, V., Carmagnola, I., & Hatton, P. V. (2014). An overview of poly (lactic-co-glycolic) acid (PLGA)-based biomaterials for bone tissue engineering. *International journal of molecular sciences*, 15(3), pp. 3640-3659.
- Guo, B., & Ma, P. X. (2014). Synthetic biodegradable functional polymers for tissue engineering: a brief review. *Science China Chemistry*, 57(4), pp. 490-500.
- Habibi, Y., & Lucia, L. A. (2012). *Polysaccharide building blocks: a sustainable approach to the development of renewable biomaterials*. John Wiley & Sons.
- Han, J., Zhou, Z., Yin, R., Yang, D., & Nie, J. (2010). Alginate–chitosan/hydroxyapatite polyelectrolyte complex porous scaffolds: Preparation and characterization. *International journal of biological macromolecules*, 46(2), pp. 199-205.
- Hendriks, F. M., Brokken, D., Oomens, C. W. J., Bader, D. L., & Baaijens, F. P. T. (2006). The relative contributions of different skin layers to the mechanical behavior of human skin in vivo using suction experiments. *Medical engineering & physics*, 28(3), pp. 259-266.
- Hiemstra, C. (2007). *In situ forming biodegradable hydrogels and their application for protein delivery*: University of Twente: Ph.D. Thesis.
- Honary, S., Maleki, M., & Karami, M. (2009). The effect of chitosan molecular weight on the properties of alginate/chitosan microparticles containing prednisolone. *Tropical Journal of Pharmaceutical Research*, 8(1), pp. 53-61.
- Jayakumar, R., Prabakaran, M., & Muzzarelli, R. A. (Eds.). (2011). *Chitosan for biomaterials I* (Vol. 243). Springer.
- Jin, R. M., Sultana, N., Baba, S., Hamdan, S., & Ismail, A. F. (2015). Porous pcl/chitosan and nha/pcl/chitosan scaffolds for tissue engineering applications: fabrication and evaluation. *Journal of Nanomaterials*, 16(1), pp. 138.

- Kementerian Kesihatan Malaysia.(2015). Kempen “YB Jom Ikrar! Derma Organ” Sempena Persidangan Parlimen 2015[Press release]. Retrieved July 8, 2017, from http://www.moh.gov.my/index.php/database_stores/attach_download/337/658
- Khan, M. A. M., Kumar, S., Ahamed, M., Alrokayan, S. A., & AlSalhi, M. S. (2011). Structural and thermal studies of silver nanoparticles and electrical transport study of their thin films. *Nanoscale research letters*, 6(1), pp. 1-8.
- Kim, S. K. (Ed.). (2013). *Chitin and chitosan derivatives: Advances in drug discovery and developments*. CRC Press.
- Kim, Y. B., & Kim, G. H. (2015). PCL/alginate composite scaffolds for hard tissue engineering: fabrication, characterization, and cellular activities. *ACS combinatorial science*, 17(2), pp. 87-99.
- Kulig, D., Zimoch-Korzycka, A., Jarmoluk, A., & Marycz, K. (2016). Study on Alginate–Chitosan Complex Formed with Different Polymers Ratio. *Polymers*, 8(5), pp. 167.
- Kumar, H., & Rani, R. (2013). Structural characterization of silver nanoparticles synthesized by micro emulsion route. *International Journal of Engineering and Innovative Technology (IJEIT)*, 3.
- Kumbar, S., Laurencin, C., & Deng, M. (2014). *Natural and Synthetic Biomedical Polymers*: Newnes.
- Kumbhar, S. G., & Pawar, S. H. (2016). Facile synthesis, characterization and antimicrobial activity of chitosan-Alginate scaffolds. *Indian Journal of Applied Research*, 5(6).
- Kuo, C. K., & Ma, P. X. (2008). Maintaining dimensions and mechanical properties of ionically crosslinked alginate hydrogel scaffolds in vitro. *Journal of Biomedical Materials Research Part A*, 84(4), pp. 899-907.
- Kyzas, G. Z., Kostoglou, M., Lazaridis, N. K., & Bikiaris, D. N. (2013). Decolorization of Dyeing Wastewater Using Polymeric Absorbents-An Overview. In *Eco-Friendly Textile Dyeing and Finishing*. InTech.
- Lanza, R., Langer, R., & Vacanti, J. P. (Eds.). (2011). *Principles of tissue engineering*. Academic press

- Lee, K. Y., & Mooney, D. J. (2012). Alginate: properties and biomedical applications. *Progress in polymer science*, 37(1), pp. 106-126.
- Li, Z. (2007). *Hybrid chitosan-alginate scaffolds for bone and cartilage tissue engineering*. University of Washington: Ph.D. Thesis.
- Loh, X. J. (2015). *In-Situ Gelling Polymers*. Springer Singapore.
- Madaghiele, M., Demitri, C., Sannino, A., & Ambrosio, L. (2014). Polymeric hydrogels for burn wound care: Advanced skin wound dressings and regenerative templates. *Burns & trauma*, 2(4), pp. 153.
- Maji, K., Dasgupta, S., Pramanik, K., & Bissoyi, A. (2016). Preparation and evaluation of gelatin-chitosan-nanobioglass 3D porous scaffold for bone tissue engineering. *International journal of biomaterials*, 2016.
- McHugh, K. J., Tao, S. L., & Saint-Geniez, M. (2013). A novel porous scaffold fabrication technique for epithelial and endothelial tissue engineering. *Journal of Materials Science: Materials in Medicine*, 24(7), pp. 1659-1670.
- Malesu, V. K., Sahoo, D., & Nayak, P. (2011). Chitosan–sodium alginate nanocomposites blended with Cloisite 30b as a novel drug delivery system for anticancer Drug curcumin.
- Malina, D., Sobczak-Kupiec, A., Wzorek, Z., & Kowalski, Z. (2012). Silver Nanoparticles Synthesis With Different Concentrations Of Polyvinylpyrrolidone. *Digest Journal of Nanomaterials and Biostructures*, 7, pp. 1527-1534.
- Matsumoto, T. (2007). Skin biomechanics from microscopic viewpoint: Mechanical properties and their measurement of horny layer, living epidermis, and dermis. *Fragrance Journal*, 35(2), pp. 36.
- Meyer, U., Handschel, J., Meyer, T., & Wiesmann, H. P. (2009). *Fundamentals of tissue engineering and regenerative medicine*: Springer.
- Mirzaei, A., Janghorban, K., Hashemi, B., Bonyani, M., Leonardi, S. G., & Neri, G. (2017). Characterization and optical studies of PVP-capped silver nanoparticles. *Journal of Nanostructure in Chemistry*, 7(1), pp. 37-46.
- Mitra, T., Sailakshmi, G., Gnanamani, A., & Mandal, A. B. (2013). Studies on cross-linking of succinic acid with chitosan/collagen. *Materials Research*, 16(4), pp. 755-765.

- Mushi, N. E. (2014). *Chitin nanofibers, networks and composites: Preparation, structure and mechanical properties*. KTH Royal Institute of Technology: Ph.D. Thesis.
- Nielsen, S. S. (Ed.). (2010). *Food analysis*. Springer.
- O'brien, F. J. (2011). Biomaterials & scaffolds for tissue engineering. *Materials today*, 14(3), pp. 88-95.
- Orlando, G., Soker, S., Stratta, R. J., & Atala, A. (2013). Will regenerative medicine replace transplantation?. *Cold Spring Harbor perspectives in medicine*, 3(8).
- Park, J. B. (2011). The use of hydrogels in bone-tissue engineering. *Med Oral Patol Oral Cir Bucal*, 16(1), pp. 115-118.
- Patel, H., Bonde, M., & Srinivasan, G. (2011). Biodegradable polymer scaffold for tissue engineering. *Trends Biomater Artif Organs*, 25(1), pp. 20-29.
- Pieróg, M., Gierszewska-Drużyńska, M., & Ostrowska-Czubenko, J. (2009). Effect of ionic crosslinking agents on swelling behavior of chitosan hydrogel membranes. *Progress on Chemistry and Application of Chitin and its Derivatives*. Polish Chitin Society, 14.
- Rajan, M., Raj, V., Al-Arfaj, A. A., & Murugan, A. M. (2013). Hyaluronidase enzyme core-5-fluorouracil-loaded chitosan-PEG-gelatin polymer nanocomposites as targeted and controlled drug delivery vehicles. *International journal of pharmaceutics*, 453(2), pp. 514-522.
- Ramli, R. H., Soon, C. F., & Rus, A. Z. M. (2016). Synthesis of Chitosan/Alginate/Silver Nanoparticles Hydrogel Scaffold. In *MATEC Web of Conferences* 78, pp 01031.
- Rasa, A. (2014). Applying dynamic mechanical analysis to research & development for viscoelastic damping materials. In *INTER-NOISE and NOISE-CON Congress and Conference Proceedings*, 249 (5), pp. 2959-2968.
- Rashid, M. U., Bhuiyan, M. K. H., & Quayum, M. E. (2013). Synthesis of silver nano particles (Ag-NPs) and their uses for quantitative analysis of vitamin C tablets. *Dhaka University Journal of Pharmaceutical Sciences*, 12(1), pp. 29-33.
- Robinson, J. W., Frame, E. S., & Frame II, G. M. (2014). *Undergraduate instrumental analysis*. CRC Press.
- Rodríguez-Vázquez, M., Vega-Ruiz, B., Ramos-Zúñiga, R., Saldaña-Koppel, D. A., & Quiñones-Olvera, L. F. (2015). Chitosan and its potential use as a scaffold

for tissue engineering in regenerative medicine. *BioMed research international*, 2015.

- Rouchi, A. H., & Mahdavi-Mazdeh, M. (2015). Regenerative medicine in organ and tissue transplantation: shortly and practically achievable?. *International journal of organ transplantation medicine*, 6(3), pp. 93.
- Roy, P., & Sailaja, R. R. N. (2015). Chitosan–nanohydroxyapatite composites: Mechanical, thermal and bio-compatibility studies. *International journal of biological macromolecules*, 73, pp. 170-181.
- Saarai, A., Kasparkova, V., Sedlacek, T., & Saha, P. (2011). A comparative study of crosslinked sodium alginate/gelatin hydrogels for wound dressing. *Recent Researches in Geography, Geology, Energy, Environment and Biomedicine*, pp. 384-389.
- Saikia, C., Gogoi, P., & Maji, T. K. (2015). Chitosan: A Promising Biopolymer in Drug Delivery Applications. *Journal of Molecular and Genetic Medicine*, 2015.
- Salehi, M., Naseri Nosar, M., Amani, A., Azami, M., Tavakol, S., & Ghanbari, H. (2015). Preparation of pure PLLA, pure chitosan, and PLLA/chitosan blend porous tissue engineering scaffolds by thermally induced phase separation method and evaluation of the corresponding mechanical and biological properties. *International Journal of Polymeric Materials and Polymeric Biomaterials*, 64(13), pp. 675-682.
- Sámano-Valencia, C., Martínez-Castañón, G. A., Martínez-Gutiérrez, F., Ruiz, F., Toro-Vázquez, J. F., Morales-Rueda, J. A., & Martínez, N. (2014). Characterization and biocompatibility of chitosan gels with silver and gold nanoparticles. *Journal of Nanomaterials*, 2014, pp. 142.
- Sawyer, L., Grubb, D. (2012). *Polymer microscopy*. Springer Science & Business Media.
- Schwartz, M. (2008). *Smart materials*: CRC Press.
- Sethuraman, S., Krishnan, U. M., & Subramanian, A. (Eds.). (2016). *Biomaterials and Nanotechnology for Tissue Engineering*. CRC Press.
- Sharma, R., Bisen, D., Shukla, U., & Sharma, B. (2012). X-ray diffraction: a powerful method of characterizing nanomaterials. *Recent Research in Science and Technology*, 4(8).

- Singh, S., Kumar, M., Singh, T., & Tyagi, L. (2011). Hydrogels used as a potential drug delivery system: A review. *International Journal of Pharmaceutical & Biological Archives*, 2(4), pp. 1068-1076.
- Song, Y. J., Wang, M., Zhang, X. Y., Wu, J. Y., & Zhang, T. (2014). Investigation on the role of the molecular weight of polyvinyl pyrrolidone in the shape control of high-yield silver nanospheres and nanowires. *Nanoscale research letters*, 9(1), pp. 17.
- Steinhoff G., (2016). *Regenerative medicine- from protocol to patient: 5. Regenerative therapies II*. Springer Science.
- Straccia, M. C., d'Ayala, G. G., Romano, I., Oliva, A., & Laurienzo, P. (2015). Alginate hydrogels coated with chitosan for wound dressing. *Marine drugs*, 13(5), pp. 2890-2908.
- Stuart, B. H. (2008). *Polymer analysis* (Vol. 30): John Wiley & Sons.
- Sun, J., & Tan, H. (2013). Alginate-based biomaterials for regenerative medicine applications. *Materials*, 6(4), pp. 1285-1309.
- Sunatkari, A. L., Talwatkar, S. S., Tamgadge, Y. S., & Muley, G. G. (2015). Influence of Surface Passivation by L-Arginine on Linear and Nonlinear Optical Properties of Ag-PVP Nanocomposite. *American Journal of Materials Science*, 5(3A), pp. 21-30.
- Szymańska, E., & Winnicka, K. (2015). Stability of Chitosan—A Challenge for Pharmaceutical and Biomedical Applications. *Marine drugs*, 13(4), pp. 1819-1846.
- Tan, H., & Marra, K. G. (2010). Injectable, biodegradable hydrogels for tissue engineering applications. *Materials*, 3(3), pp. 1746-1767.
- Tang, L., Thevenot, P., & Hu, W. (2008). Surface chemistry influences implant biocompatibility. *Current topics in medicinal chemistry*, 8(4), pp. 270-280.
- Tanigawa, J., Miyoshi, N., & Sakurai, K. (2008). Characterization of chitosan/citrate and chitosan/acetate films and applications for wound healing. *Journal of applied polymer science*, 110(1), pp. 608-615.
- Tateishi, T. (2008). *Biomaterials in Asia: In Commemoration of the 1st Asian Biomaterials Congress, Tsukuba, Japan, 6-8 December 2007*. World Scientific.
- Theivasanthi, T., & Alagar, M. (2011). Electrolytic synthesis and characterizations of silver nanopowder. *Nano Biomedicine and Engineering*, 4(2), pp. 58-65..

- Theocharis, A. D., Skandalis, S. S., Gialeli, C., & Karamanos, N. K. (2016). Extracellular matrix structure. *Advanced drug delivery reviews*, 97, pp. 4-27.
- Thi Hiep, N., Chan Khon, H., Dai Hai, N., Byong-Taek, L., Van Toi, V., & Thanh Hung, L. (2017). Biocompatibility of PCL/PLGA-BCP porous scaffold for bone tissue engineering applications. *Journal of Biomaterials Science, Polymer Edition*, 28(9), pp. 864-878.
- Thomas, S., Grohens, Y., & Ninan, N. (2015). *Nanotechnology Applications for Tissue Engineering*: William Andrew.
- Thomas, S., Durand, D., Chassenieux, C., & Jyotishkumar, P. (Eds.). (2013). *Handbook of biopolymer-based materials: from blends and composites to gels and complex networks*. John Wiley & Sons.
- Thwala, L. N. (2012). *Preparation and characterization of alginate-chitosan nanoparticles as a drug delivery system for lipophilic compounds*. University of Johannesburg: Ph.D. Thesis.
- Trachtenberg, J. E., Placone, J. K., Smith, B. T., Fisher, J. P., & Mikos, A. G. (2017). Extrusion-based 3D printing of poly (propylene fumarate) scaffolds with hydroxyapatite gradients. *Journal of Biomaterials Science, Polymer Edition*, 28(6), pp. 532-554.
- Trivedi, M. (2015). Characterization of physicochemical and thermal properties of chitosan and sodium alginate after biofield treatment. *Pharmaceutica Analytica Acta-Open Access*, 6(10).
- Upadhyay, R. K. (2015). Role of regeneration in tissue repairing and therapies. *Journal of Regenerative Medicine and Tissue Engineering*, 4(1), pp. 1.
- U.S. Department of Health & Human Services (2016). U.S. Department of Health & Services. Retrieved on May 20, 2016, from <https://optn.transplant.hrsa.gov/>.
- Varkey, M., Ding, J., & Tredget, E. E. (2015). Advances in skin substitutes—potential of tissue engineered skin for facilitating anti-fibrotic healing. *Journal of functional biomaterials*, 6(3), pp. 547-563.
- Venkatesan, J., Bhatnagar, I., & Kim, S.-K. (2014). Chitosan-alginate biocomposite containing fucoidan for bone tissue engineering. *Marine drugs*, 12(1), pp. 300-316.
- Vishwakarma, A., Sharpe, P., Shi, S., & Ramalingam, M. (Eds.). (2014). *Stem cell biology and tissue engineering in dental sciences*. Academic Press.

- Walters, K. A., & Roberts, M. S. (2002). The structure and function of skin. *Drugs and the pharmaceutical Sciences*, 119, pp. 1-40.
- Wilburn, F. W. (1989). Introduction to thermal analysis, techniques and applications: Michael E. Brown. Chapman and Hall, London.
- Wong, J. (2013). *Synthesis and characterisation of chitosan from shrimp shells*. Universiti Tunku Abdul Rahman: Degree's Project Report.
- Yahia, L., Chirani, N., Gritsch, L., Motta, F. L., & Fare, S. (2015). History and applications of hydrogels. *Journal of biomedical sciences*, 4(2).
- Yan, Y., Zhang, X., Li, C., Huang, Y., Ding, Q., & Pang, X. (2015). Preparation and characterization of chitosan-silver/hydroxyapatite composite coatings on TiO₂ nanotube for biomedical applications. *Applied Surface Science*, 332, pp. 62-69.
- Yao, H., & Kimura, K. (2007). Field emission scanning electron microscopy for structural characterization of 3D gold nanoparticle superlattices. *Modern research and educational topics in microscopy*.
- Yue, B. (2014). Biology of the extracellular matrix: an overview. *Journal of glaucoma*, 2014, pp. 20-23.
- Zhang, X. C. (Ed.). (2016). *Science and Principles of Biodegradable and Bioresorbable Medical Polymers: Materials and Properties*. Woodhead Publishing.
- Zhao, F., Yao, D., Guo, R., Deng, L., Dong, A., & Zhang, J. (2015). Composites of polymer hydrogels and nanoparticulate systems for biomedical and pharmaceutical applications. *Nanomaterials*, 5(4), pp. 2054-2130.
- Zhao, J., Han, W., Chen, H., Tu, M., Zeng, R., Shi, Y., Zhou, C. (2011). Preparation, structure and crystallinity of chitosan nano-fibers by a solid-liquid phase separation technique. *Carbohydrate Polymers*, 83(4), pp 1541-1546.
- Zhu, J. (2010). Bioactive modification of poly (ethylene glycol) hydrogels for tissue engineering. *Biomaterials*, 31(17), pp. 4639-4656.
- Zhu, J., & Marchant, R. E. (2011). Design properties of hydrogel tissue-engineering scaffolds. *Expert review of medical devices*, 8(5), pp. 607-626.
- Zucolotto, V. (2013). *Nanotoxicology: materials, methodologies, and assessments*. Springer Science & Business Media.